

INSTRUCTIONS FOR MAINTENANCE OF COLORED AND PROTECTIVE FILMS

Refrain from washing your vehicle (not even manual washing) for three to five days after the application of film. Occasional bubbles under the film may appear at the time of acceptance, which will disappear on their own in around a month's time, depending on the ambient temperature. Never puncture them and do not try to remove them by other means! When you experience a problem or a defect, contact the WrapStyle installation center. Adhere to regular warranty inspections! The wrapped vehicle may be routinely cleaned in car wash without any restrictions; in case of washing the vehicle by hand, tell the operator how to wash and care for the film. However, special textured, matte or chrome films require special maintenance; inquire at our branches for more information. Protective films are specific in that they are glued on top of water supplemented with a special applicator or gel. Occasional bubbles and places with remains of water, slight milky tint or spots may appear under the film. This is completely normal and not a defect preventing acceptance of the completed work. The water and any bubbles will disappear after a month or two (depending on the ambient temperature) on their own, the water will dry out, the film will fit and stretch. In the winter, it is necessary to let the water dry in order to avoid freezing and possible damage to the film. Extra care must be taken when using pressure washers since it is a self-adhesive film; if the pressure induced on the film is too large, it can cause damage or tear the film; especially in winter months when the film is crisp. Therefore, use high pressure washers with extreme caution and keep the high-pressure nozzle away from the car! Careless washing with pressure washers is the most common cause of damage to the film by the owner. Only ever use soft terry towels or microfiber towels for mechanical cleaning and washing of the wrapped parts of the vehicle. The film must not be wiped or scrubbed when exposed to direct sunlight or while the film is warm. Do not use any cleaners, waxes, sealants and other chemicals on the film that are not pre-approved by WrapStyle. It is recommended to treat the film at least once every two months, or even more often during unfavorable weather conditions.

Only use car cosmetics from WrapStyle for maintenance, which can be purchased at any WrapStyle branch. Car cosmetics for varnish contain pigments and other aggressive chemicals, such as naphtha, kerosene or solvents, and may cause discoloration or loss of film gloss, or other damage that cannot be removed. We recommend you to have this procedure done by professionals, preferably with experience in maintenance of car films. In the event of damage to the foil (abrasions, scratches) localized fixes are possible, i.e. the damaged part is cut out and a patch is pasted in or the entire part where the damage occurred is wrapped again. Both methods will solve the problem, it is only about appearance. Lifetime of the film (in years): metallic colors 2-4 years; color 3-5 years, textured (carbon, faceted etc.) 2-3 years, chromium 1-2 years, protective 3-5 years. Lifetime of the film depends on the conditions and method of use, garaging, regular maintenance and care; the recommended time for removal of the film is 3 years. The film has a lifetime and partial loss of pigment may occur after a few months.

Car cosmetics for varnish contain pigments and other aggressive chemicals, such as naphtha, kerosene or solvents, and may cause discoloration or loss of film gloss, or other damage that cannot be removed. We recommend you to have this procedure done by professionals, preferably with experience in maintenance of car films. In the event of damage to the foil (abrasions, scratches) localized fixes are possible, i.e. the damaged part is cut out and a patch is pasted in or the entire part where the damage occurred is wrapped again. Both methods will solve the problem, it is only about appearance. Lifetime of the film (in years): metallic colors 2-4 years; color 3-5 years, textured (carbon, faceted etc.) 2-3 years, chromium 1-2 years, protective 3-5 years. Lifetime of the film depends on the conditions and method of use, garaging, regular maintenance and care; the recommended time for removal of the film is 3 years. The film has a lifetime and partial loss of pigment may occur after a few months.

WrapStyle is not responsible for manufacturer's warranty for the film and doesn't guarantee color consistency throughout the warranty period.

WARNING: Never use machine polishing, grinding or other gross mechanical cleaning for the films! The film would lose its unique look and it might incur shiny patches or scratches. For film maintenance, use only WrapStyle car cosmetics, developed specifically for the care of these special vehicle surfaces. All films must be regularly cleaned, serviced and maintained in good condition. In the event of damage to the film as a result of collision not caused by you, you are entitled to payment for repair of the damaged part of the film by the insurance company of the offending driver, according to the applicable rules of insurance. In the case of accident insurance, it is recommended to inform your insurance company about the installation of your car wrap and contact them for more information. The film is homologated, non-flammable and self-extinguishing. The film can be removed without residue and without damage to car paint. We bear no responsibility in case of damage to paintwork when removing the film from a poor, non-genuine or older paintwork that was already damaged.

CLEANING AND MAINTENANCE OF WINDOW FILM

Windows fitted with films are washed in a completely regular manner using shampoos, lotions, rubber spatulas, etc. You cannot use thinners, solvents, corrosive chemicals, sharp and hard objects (screwdrivers, wire nails, cleaning sand, etc.). Refrain from washing or rolling down windows for 48 hours after installation!